

TECHNICAL DATA SHEET

COADIS™ 234 K

Synthetic versatile dispersant for water-borne systems

Ionic Copolymer dispersant

TYPICAL CHARACTERISTICS

Nature	Potassium salt of polycarboxylic polymer in aqueous solution
Appearance	Amber liquid
Solid Content (%)	24
Active Content (%)	24
pH	10
Brookfield viscosity (mPa.s)	1500
Specific gravity	1.08
Neutralization type	Potassium
Solvent	Water

DESCRIPTION

Coadis™ 234 K is a synthetic versatile dispersant for waterborne systems. Its use is recommended for a wide application field, including flat to glossy dispersion paints, thick film coating and plasters, and also organic pigment pastes (e.g. carbon black dispersion).

RECOMMENDED ADDITION LEVEL

It requires levels of use between 0.1% and 1% (dry product on total formulation weight) and more often between 0.1% and 0.5% (e.g in renderings, in flat and gloss dispersion paints. Level of use are higher for the formulation of organic pigment pastes and can reach until 15% for a carbon black dispersion (dry product on pigment weight)

STANDARD PACKAGING

- Other packaging may be available upon request
- 1000L IBC
 - 220L Drum
 - Bulk

HANDLING & STORAGE

It should be protected from the effects of weathering and stored between 5 and 40°C.

Once opened, packaging should be resealed immediately after use. In these conditions, this product should be used within 12 months from delivery.

HEALTH AND ENVIRONMENTAL DATA

For safe handling please refer to the Safety Data Sheet. For more information about health and environmental data, please contact us.

MARKETS

Composites & Advanced Materials

- Graphic Arts

Coatings & Inks

- Architectural Coating
- Industrial Coating
- Textile & Leather Coating

KEY BENEFITS

FORMULATION

- Compatibility
- Post addition
- Ready to use



STORAGE

- Floating resistance
- Syneresis resistance
- Antisettling
- Viscosity stability



FILM PROPERTIES

- Anticorrosion
- Stain resistance
- Water resistance



SAFER SOLUTIONS

- APEO Free*
- Heavy Metal Free*
- Solvent Free*

* Not intentionally added but not specifically measured (not part of product specification)

PVC

- PVC Low
- PVC Mid
- PVC High



SUITABLE FOR

- Inorganic pigments
- Organic pigments
- Fillers



Headquarters: Arkema France
51, Esplanade du Général de Gaulle
92800 Puteaux – France
T +33 (0)1 49 00 80 80