

TECHNICAL DATA SHEET

COADIS™ 615

Dispersing agent for industrial coatings

Non ionic dispersant

TYPICAL CHARACTERISTICS

Nature	High molecular weight polycarboxylate copolymer
Appearance	Yellow to brownish liquid
Solid Content (%)	40
Active Content (%)	40
pH	4
Specific gravity	1.07
Neutralization type	Sodium
Solvent	Water

DESCRIPTION

Coadis™ 615 is a water-based synthetic polycarboxylate dispersant that has been specially designed for industrial coatings and reactive binder systems.

STANDARD PACKAGING

Other packaging may be available upon request

- 1000L IBC
- 220L Drum
- Bulk

HANDLING & STORAGE

It should be protected from the effects of weathering and stored between 5 and 40°C.

Once opened, packaging should be resealed immediately after use.

In these conditions, this product should be used within 12 months from delivery.

HEALTH AND ENVIRONMENTAL DATA

For safe handling please refer to the Safety Data Sheet. For more information about health and environmental data, please contact us.

MARKETS

Coatings & Inks

- Architectural Coating
- Industrial Coating

KEY BENEFITS

FORMULATION

- Compatibility
- Easy handling
- Ready to use



STORAGE

- Antisettling
- Floating resistance
- Viscosity stability
- Syneresis resistance



FILM PROPERTIES

- Anticorrosion
- Water resistance
- Hiding power/Opacity



SAFER SOLUTIONS

- APEO Free*
- Heavy Metal Free*
- Solvent Free*

* Not intentionally added but not specifically measured (not part of product specification)

PVC

PVC Low
PVC Mid
PVC High



SUITABLE FOR

Inorganic pigments
Fillers
Organic pigments



Headquarters: Arkema France
51, Esplanade du Général de Gaulle
92800 Puteaux – France
T +33 (0)1 49 00 80 80