

TECHNICAL DATA SHEET

ENCOR® 2722

Acrylic Emulsion

PRODUCT APPLICATION DETAILS

ENCOR® 2722 is a premium APEO-free acrylic emulsion engineered to deliver exceptional tannin-blocking performance without relying on zinc oxide. Designed specifically for waterborne wood coatings, it provides excellent sand-ability, strong adhesion, and reliable stain-blocking properties—making it an ideal choice for high-quality industrial wood and architectural primers and sealers.

SALES SPECIFICATIONS

	CHARACTERISTICS	METHODS
Solid content	41-43 %	
pH	8.5 -9,5	
Viscosity	<1000 cP	

OTHER CHARACTERISTICS¹

	CHARACTERISTICS	METHODS
Appearance	Opaque	
Minimum film formation temperature	<5 °C	
Density	8.7 lbs/gal	

¹The data provided for these properties are typical values, intended only as guides, and should not be construed as sales specifications

MARKETS

Coatings & Inks

- Architectural Coating
 - Primers
 - Architectural Wood
- Industrial Coating
 - Wood Furniture
 - Wood Joinery
 - Industrial Wood Finishes

PERFORMANCE BENEFITS

- Excellent Tannin Blocking Properties Without Zinc Oxide
- Good Sandability
- APE Free
- Low VOC (<100g/L) Paints

ENCOR[®] 2722

ENCOR[®] 2722

Arkema Coating Resins
410 Gregson Dr.
Cary, NC 27511 – USA
T +1 919 469 6700

Headquarters: Arkema France
51, Esplanade du Général de Gaulle
92800 Puteaux – France
T +33 (0)1 49 00 80 80

Disclaimer - Please consult Arkema's disclaimer regarding the use of Arkema's products on <https://www.arkema.com/global/en/products/product-safety/disclaimer/> which is incorporated herein by reference and made a part hereof.
Arkema France, a French société anonyme registered at the Trade and Companies Register of Nanterre under the number 319 632 790

[arkema.com](https://www.arkema.com)

ARKEMA