

TECHNICAL DATA SHEET

ENCOR[®] 2746

Acrylic Emulsion

PRODUCT APPLICATION DETAILS

ENCOR 2746 is a 100% acrylic resin at 50% solids content, designed for exterior architectural coating applications. ENCOR 2746 offers scrub resistance, dirt pick-up resistance, gloss retention, surfactant leaching resistance, block resistance, and multi-substrate adhesion and is APEO free and low VOC capable (0-50 g/L).

SALES SPECIFICATIONS

	CHARACTERISTICS	METHODS
Solid content	50 %	
pH	8.2	
Viscosity (#3 spindle @ 60 rpm. Brookfield LV)	100 cP	

OTHER CHARACTERISTICS¹

	CHARACTERISTICS	METHODS
Minimum film formation temperature	10 °C	

¹The data provided for these properties are typical values, intended only as guides, and should not be construed as sales specifications

MARKETS & APPLICATIONS

COATINGS & INKS

- ARCHITECTURAL COATING
 - EXTERIOR WALL

ENCOR® 2746

ENCOR® 2746

Headquarters: Arkema France
51, Esplanade du Général de Gaulle
92800 Puteaux – France
T +33 (0)1 49 00 80 80

Disclaimer - Please consult Arkema's disclaimer regarding the use of Arkema's products on <https://www.arkema.com/global/en/products/product-safety/disclaimer/> which is incorporated herein by reference and made a part hereof.
Arkema France, a French société anonyme registered at the Trade and Companies Register of Nanterre under the number 319 632 790

[arkema.com](https://www.arkema.com)

