

## TECHNICAL DATA SHEET

# ETHACRYL™ SR

PolyCarboxylate ether for concrete admixtures

### TYPICAL CHARACTERISTICS

Nature	<b>Aqueous solution of Polycarboxylate Ether</b>
Appearance	<b>Colourless to yellowish liquid</b>
Solid Content (%)	<b>40</b>
pH	<b>3.9</b>
Specific gravity	<b>1.07</b>

### DESCRIPTION

Breaking the limits of High Slump Retention with high Water Reducing effect: Ethacryl™ SR is a slump keeping polycarboxylate superplasticizer, designed for High Slump Retention, at a very low dosage. It enables the formulator to achieve an excellent control of the fluidity over the time. Ethacryl™ SR is a new generation of high-performance aqueous dispersant designed for to be used alone in concrete applications. Ethacryl™ SR is a high Water Reducing agent (>25%). Ethacryl™ SR is a key component for formulating concrete admixtures. Benefits include productivity, lower costs and improved concrete properties.

### RECOMMENDED ADDITION LEVEL

0.1 to 2.00% in relation to weight of cement

### STANDARD PACKAGING

Other packaging may be available upon request

- 1000L IBC
- Bulk

### HANDLING & STORAGE

The product can present colour variations from light yellow to slightly brown. These variations can occur in normal storage conditions. They have no influence on the product performances. The product should be protected from the effects of weathering and stored between 5 and 40°C. In these conditions, this product should be used within 12 months from delivery.

### PROCESSING INSTRUCTIONS

Ethacryl™ is added either, together with mixing water, either delayed in previously wet concrete with a fraction of the mixing water.

### HEALTH AND ENVIRONMENTAL DATA




For safe handling please refer to the Safety Data Sheet. For more information about health and environmental data, please contact us.

### MARKETS

#### Building & Construction

- Construction Materials
- Concrete

### KEY BENEFITS

- Alkali content < 1.5
- Chloride content (%) < 0.01
- Foam control additives No
- Slump reduction 
- Water reduction 
- Workability 

**Headquarters: Arkema France**  
51, Esplanade du Général de Gaulle  
92800 Puteaux – France  
T +33 (0)1 49 00 80 80

Disclaimer - Please consult Arkema's disclaimer regarding the use of Arkema's products on <https://www.arkema.com/global/en/products/product-safety/disclaimer/> which is incorporated herein by reference and made a part hereof.

Arkema France, a French société anonyme registered at the Trade and Companies Register of Nanterre under the number 319 632 790  
**arkema.com**