

TECHNICAL DATA SHEET

Poly AK[®] QA1190BASE

PRODUCT APPLICATION DETAILS

Poly AK QA-1190 is an acrylic copolymer specifically designed as a pressure-sensitive adhesive and for the production of adhesives that can be used in a variety of applications, as it possesses special properties and characteristics.
Has excellent mechanic stability
The product forms a pressure sensitive film

SALES SPECIFICATIONS

	CHARACTERISTICS	METHODS
Solid content	54.0 - 57.0 %	Internal method
pH	4.0 - 5.5	Internal method
Viscosity	200 - 500 cP	Internal method

OTHER CHARACTERISTICS¹

	CHARACTERISTICS	METHODS
Appearance	Milky white emulsion	
Density	1.02 g.cm	
Average particle size	0.35 microns	
Ionic charge	Anionic	

¹The data provided for these properties are typical values, intended only as guides, and should not be construed as sales specifications

MARKETS & APPLICATIONS

COATINGS & INKS

- ARCHITECTURAL COATING
- EXTERIOR PAINTS

POLY AK® QA1190BASE

STORAGE AND HANDLING

Poly AK® QA1190BASE Under normal conditions, the product has excellent stability. It is advisable to keep it indoors and away from sources of heat and UV radiation. We recommend using this product within 6 months of storage.
Shelf Life (Months): 6

Headquarters: Arkema France
51, Esplanade du Général de Gaulle
92800 Puteaux – France
T +33 (0)1 49 00 80 80

Disclaimer - Please consult Arkema's disclaimer regarding the use of Arkema's products on <https://www.arkema.com/global/en/products/product-safety/disclaimer/> which is incorporated herein by reference and made a part hereof.
Arkema France, a French société anonyme registered at the Trade and Companies Register of Nanterre under the number 319 632 790