

TECHNICAL DATA SHEET

Poly AK® QA190

PRODUCT APPLICATION DETAILS

Poly AK QA-190 is a copolymer of acrylic and polyurethane, specifically designed for the formulation of hybrid waterproofing products, as it possesses superior properties and characteristics.

Has excellent mechanic stability

The product forms a flexible film

SALES SPECIFICATIONS

	CHARACTERISTICS	METHODS
Solid content	46.5 - 48.5 %	Internal method
pH	6.5 - 8.0	Internal method
Viscosity	100 - 800 cP	Internal method

OTHER CHARACTERISTICS¹

	CHARACTERISTICS	METHODS
Appearance	Blueish white emulsion	
Density	1.02 g.cm	
Average particle size	0.23 microns	
Ionic charge	Non anionic	

¹The data provided for these properties are typical values, intended only as guides, and should not be construed as sales specifications

MARKETS & APPLICATIONS

COATINGS & INKS

- ARCHITECTURAL COATING
- EXTERIOR PAINTS

POLY AK[®] QA190

STORAGE AND HANDLING

Poly AK[®] QA190 Under normal conditions, the product has excellent stability. It is advisable to keep it indoors and away from sources of heat and UV radiation. We recommend using this product within 6 months of storage.
Shelf Life (Months): 6

Headquarters: Arkema France
51, Esplanade du Général de Gaulle
92800 Puteaux – France
T +33 (0)1 49 00 80 80

Disclaimer - Please consult Arkema's disclaimer regarding the use of Arkema's products on <https://www.arkema.com/global/en/products/product-safety/disclaimer/> which is incorporated herein by reference and made a part hereof.
Arkema France, a French société anonyme registered at the Trade and Companies Register of Nanterre under the number 319 632 790