

TECHNICAL DATA SHEET

Poly KAS[®] QA166

PRODUCT APPLICATION DETAILS

Poly KAS QA-166 is a carboxylic acrylic terpolymer that modifies the rheology and viscosity of paint and coatings by pre-establishing an alkaline pH. Its rheological behavior gives paints and coatings improved film formation, fluidity, leveling, and increased gloss. Has excellent mechanic stability

SALES SPECIFICATIONS

	CHARACTERISTICS	METHODS
Solid content	29.0 - 31.0 %	Internal method
pH	2.5 - 4.0	Internal method
Viscosity	5 - 30 cP	Internal method

OTHER CHARACTERISTICS¹

	CHARACTERISTICS	METHODS
Appearance	Milky white liquid	
Density	1.05 g.cm	
Ionic charge	Anionic	

¹The data provided for these properties are typical values, intended only as guides, and should not be construed as sales specifications

MARKETS & APPLICATIONS

COATINGS & INKS

- ARCHITECTURAL COATING
 - EXTERIOR PAINTS

POLY KAS® QA166

STORAGE AND HANDLING

Poly KAS® QA166 Under normal conditions, the product has excellent stability. It is advisable to keep it indoors and away from sources of heat and UV radiation. We recommend using this product within 6 months of storage.
Shelf Life (Months): 6

Headquarters: Arkema France
51, Esplanade du Général de Gaulle
92800 Puteaux – France
T +33 (0)1 49 00 80 80

Disclaimer - Please consult Arkema's disclaimer regarding the use of Arkema's products on <https://www.arkema.com/global/en/products/product-safety/disclaimer/> which is incorporated herein by reference and made a part hereof.
Arkema France, a French société anonyme registered at the Trade and Companies Register of Nanterre under the number 319 632 790