

TECHNICAL DATA SHEET

Poly VAR[®] QANYL17

PRODUCT APPLICATION DETAILS

Poly VAR QA-NYL 17 is a sodium polyacrylate developed as a high-performance dispersant, specially designed for use in the dispersion of fillers and pigments, as it has very special properties and characteristics.
The product forms a clear film
Soluble in water in any proportion.

SALES SPECIFICATIONS

	CHARACTERISTICS	METHODS
Solid content	35.0 - 37.0 %	Internal method
pH	7.5 - 8.5	Internal method
Viscosity	0 - 150 cP	Internal method

OTHER CHARACTERISTICS¹

	CHARACTERISTICS	METHODS
Appearance	Slightly cloudy liquid ranging from light to dark amber in color	
Density	1.26 g.cm	

¹The data provided for these properties are typical values, intended only as guides, and should not be construed as sales specifications

MARKETS & APPLICATIONS

COATINGS & INKS

- ARCHITECTURAL COATING
- EXTERIOR PAINTS

POLY VAR® QANYL17

STORAGE AND HANDLING

Poly VAR® QANYL17 Under normal conditions, the product has excellent stability. It is advisable to keep it indoors and away from sources of heat and UV radiation. We recommend using this product within 6 months of storage.
Shelf Life (Months): 6

Headquarters: Arkema France
51, Esplanade du Général de Gaulle
92800 Puteaux – France
T +33 (0)1 49 00 80 80

Disclaimer - Please consult Arkema's disclaimer regarding the use of Arkema's products on <https://www.arkema.com/global/en/products/product-safety/disclaimer/> which is incorporated herein by reference and made a part hereof.
Arkema France, a French société anonyme registered at the Trade and Companies Register of Nanterre under the number 319 632 790