

TECHNICAL DATA SHEET

Poly VAR® QANYL240ESP

PRODUCT APPLICATION DETAILS

The Poly VAR QANYL-240 ESP product is a sodium salt of polyacrylic acid, specially designed to be used for leather filling, since it has special properties and characteristics.
Film properties: rigid and firm

SALES SPECIFICATIONS

	CHARACTERISTICS	METHODS
Solid content	25.0 - 30.0 %	Internal method
pH	6.0 - 8.0	Internal method
Viscosity	500 - 2,000 cP	Internal method

OTHER CHARACTERISTICS¹

	CHARACTERISTICS	METHODS
Appearance	Clear amber liquid	
Density	1.14 g.cm	
Ionic charge	Anionic	

¹The data provided for these properties are typical values, intended only as guides, and should not be construed as sales specifications

MARKETS & APPLICATIONS

COATINGS & INKS

- ARCHITECTURAL COATING
- EXTERIOR PAINTS

POLY VAR® QANYL240ESP

STORAGE AND HANDLING

Poly VAR® QANYL240ESP Under normal conditions, the product has excellent stability. It is advisable to keep it indoors and away from sources of heat and UV radiation. We recommend using this product within 6 months of storage.
Shelf Life (Months): 6

Headquarters: Arkema France
51, Esplanade du Général de Gaulle
92800 Puteaux – France
T +33 (0)1 49 00 80 80

Disclaimer - Please consult Arkema's disclaimer regarding the use of Arkema's products on <https://www.arkema.com/global/en/products/product-safety/disclaimer/> which is incorporated herein by reference and made a part hereof.
Arkema France, a French société anonyme registered at the Trade and Companies Register of Nanterre under the number 319 632 790