

TECHNICAL DATA SHEET

Poly VIL® QV5045

PRODUCT APPLICATION DETAILS

Poly VIL QV-5045 is a pre-catalyzed vinyl acetate homopolymer, specially designed as an adhesive for wood, as it has very special properties and characteristics.

Has good mechanic stability

The product forms a semi-rigid film

SALES SPECIFICATIONS

	CHARACTERISTICS	METHODS
Solid content	50.0 - 52.0 %	Internal method
pH	3.0 - 5.0	Internal method
Viscosity	6,000 - 7,000 cP	Internal method

OTHER CHARACTERISTICS¹

	CHARACTERISTICS	METHODS
Appearance	White viscous emulsion	
Density	1.02 g.cm	
Ionic charge	Anionic	

¹The data provided for these properties are typical values, intended only as guides, and should not be construed as sales specifications

MARKETS & APPLICATIONS

COATINGS & INKS

- ARCHITECTURAL COATING
- EXTERIOR PAINTS

POLY VIL® QV5045

STORAGE AND HANDLING

Poly VIL® QV5045 Under normal conditions, the product has excellent stability. It is advisable to keep it indoors and away from sources of heat and UV radiation. We recommend using this product within 6 months of storage.
Shelf Life (Months): 6

Headquarters: Arkema France
51, Esplanade du Général de Gaulle
92800 Puteaux – France
T +33 (0)1 49 00 80 80

Disclaimer - Please consult Arkema's disclaimer regarding the use of Arkema's products on <https://www.arkema.com/global/en/products/product-safety/disclaimer/> which is incorporated herein by reference and made a part hereof.
Arkema France, a French société anonyme registered at the Trade and Companies Register of Nanterre under the number 319 632 790