

## TECHNICAL DATA SHEET

# RHEOTECH™ 4200

Acrylic associative thickener for water-based systems

## HASE Acrylic Thickener



29% Bio Carbon Content (only for EMEA supply)  
-22% Carbon Footprint Reduction (only for EMEA supply)

### TYPICAL CHARACTERISTICS

Nature	<b>Aqueous dispersion of an acrylic copolymer</b>
Appearance	<b>Low viscous white milky liquid</b>
Solid Content (%)	<b>30</b>
Active Content (%)	<b>30</b>
pH	<b>3</b>
Specific gravity	<b>1.06</b>
Solvent	<b>Water</b>
Total Bio content (%)	<b>29</b>

### DESCRIPTION

Rheotech™ 4200 is an associative acrylic thickener designed to improve both the rheology and the color acceptance of water based formulations.

Its outstanding effectiveness at medium shear rates allows to control very easily the perceived quality of paints during handling and to facilitate coating by roll or by bush, especially for finishing touches.

Rheotech™ 4200 ensures safe additions of colorants in water based formulations, limiting viscosity changes and rub-out issues.

Rheotech™ 4200 can be used in every kind of alkaline water based formulation and particularly in solvent and Alkyl Phenol Ethoxylate (APE) free formulations.

### STANDARD PACKAGING

Other packaging may be available upon request

- 1000L IBC
- 200L Drum
- Bulk

### HANDLING & STORAGE

It can be irreversibly altered by frost. It should be protected from the effects of weathering and stored between 5 and 40°C and protected from direct sun exposure.

Once opened, packaging should be resealed immediately after use.

Film-forming product, surface may dry in contact with air.

A slight sedimentation can be visible at the bottom of drums or totes. This phenomenon is normal and has no impact on the use and level of performance as long as the solids content of the product meets the specification. If necessary, filter the product prior to its use.

In these conditions, this product should be used within 6 months from delivery.

### HEALTH AND ENVIRONMENTAL DATA

For safe handling please refer to the Safety Data Sheet. For more information about health and environmental data, please contact us.

### MARKETS

#### Composites & Advanced Materials

- Graphic Arts

#### Coatings & Inks

- Architectural Coating
- Industrial Coating
- Textile & Leather Coating

#### Adhesives & Sealants

- Assembly
- Other Adhesives
- Sealants

### KEY BENEFITS

#### FORMULATION

- Cost in use
- Color acceptance
- Compatibility



#### STORAGE

- In-can appearance
- Syneresis resistance
- Antisettling
- Viscosity stability



#### APPLICATION

- Brushability
- Rollability
- Sag resistance



#### FILM PROPERTIES

- Rub out
- Hiding power/Opacity
- Gloss



#### SAFER SOLUTIONS


- APEO Free\*
- Heavy Metal Free\*
- LiCl Free\*
- MIT Free\*
- Solvent Free\*

\* Not intentionally added but not specifically measured (not part of product specification)

- Total Bio content (%) **29**

# RHEOTECH™ 4200

## THICKENING MECHANISM

Non Associative   
Self Association   
Associative 

## VISCOSITY CONTRIBUTION

Mid Shear contribution   
Low Shear contribution   
High Shear contribution 

## PVC

PVC Low   
PVC Mid   
PVC High 

**Headquarters: Arkema France**  
51, Esplanade du Général de Gaulle  
92800 Puteaux – France  
T +33 (0)1 49 00 80 80

Disclaimer - Please consult Arkema's disclaimer regarding the use of Arkema's products on <https://www.arkema.com/global/en/products/product-safety/disclaimer/> which is incorporated herein by reference and made a part hereof.

Arkema France, a French société anonyme registered at the Trade and Companies Register of Nanterre under the number 319 632 790

[arkema.com](https://www.arkema.com)

**ARKEMA**