

## TECHNICAL DATA SHEET

# SYNOCURE® 9483 S 50

Carboxyl acrylic NISO

### PRODUCT APPLICATION DETAILS

SYNOCURE® 9483 S 50 is an acrylic for use in topcoats where a non-isocyanate (NISO) curing system is needed, that has exterior durability, solvent resistance, hardness, adhesion, and color retention. Used for general industrial metal, structural steel and CASE coatings

### SALES SPECIFICATIONS

	CHARACTERISTICS	METHODS
Solid content	50 %	-
Viscosity	X-Z Gardner Holdt	-
Color	2 Gardner	-
Acid value	31 mg KOH/g	-

### OTHER CHARACTERISTICS<sup>1</sup>

	CHARACTERISTICS	METHODS
Solvent	Xylene/n-Butanol 80/20	-
Density	8.1 lbs/gal	-

<sup>1</sup>The data provided for these properties are typical values, intended only as guides, and should not be construed as sales specifications

### MARKETS

#### Coatings & Inks

- Industrial Coating
  - Automotive - OEM
  - General Industry
  - Protective Coating
  - Protective And Marine Coating

# SYNOCURE® 9483 S 50

## PRODUCT SAFETY

Please refer to the corresponding Safety Data Sheet.

## STORAGE AND HANDLING

SYNOCURE® 9483 S 50 should be stored indoors in the original, unopened and undamaged container, in a dry place at a temperature not exceeding 30°C. Exposure to direct sunlight should be avoided. In the above mentioned storage conditions the shelf life of the resin will be months from the shipping date.

**Arkema Coating Resins**  
410 Gregson Dr.  
Cary, NC 27511 – USA  
T +1 919 469 6700

**Headquarters: Arkema France**  
51, Esplanade du Général de Gaulle  
92800 Puteaux – France  
T +33 (0)1 49 00 80 80

Disclaimer - Please consult Arkema's disclaimer regarding the use of Arkema's products on <https://www.arkema.com/global/en/products/product-safety/disclaimer/> which is incorporated herein by reference and made a part hereof.  
Arkema France, a French société anonyme registered at the Trade and Companies Register of Nanterre under the number 319 632 790

[arkema.com](https://www.arkema.com)

**ARKEMA**