

TECHNICAL DATA SHEET

SYNOLAC® 0691 SD 60

Oil free polyester

PRODUCT APPLICATION DETAILS

SYNOLAC 0691 SD 60 is a high molecular weight thermoplastic saturated polyester, with improved resistance to crystallisation in solution with aromatic solvents. SYNOLAC 0691 SD 60 is recommended for manufacture of high reactive and elastic coil coatings top coats with good resistance to ageing, high quality base coatings with excellent mechanical properties and good chemical resistance, white enamels for collapsible tubes and spraying bottles.

MARKETS

Coatings & Inks

- Industrial Coating
 - Coil

SYNOLAC® 0691 SD 60

PRODUCT SAFETY

Please refer to the corresponding Safety Data Sheet.

STORAGE AND HANDLING

SYNOLAC® 0691 SD 60 should be stored indoors in the original, unopened and undamaged container, in a dry place at a temperature not exceeding 30°C. Exposure to direct sunlight should be avoided.
In the above mentioned storage conditions the shelf life of the resin will be from the shipping date.

Headquarters: Arkema France
51, Esplanade du Général de Gaulle
92800 Puteaux – France
T +33 (0)1 49 00 80 80

Disclaimer - Please consult Arkema's disclaimer regarding the use of Arkema's products on <https://www.arkema.com/global/en/products/product-safety/disclaimer/> which is incorporated herein by reference and made a part hereof.
Arkema France, a French société anonyme registered at the Trade and Companies Register of Nanterre under the number 319 632 790

[arkema.com](https://www.arkema.com)

ARKEMA