

TECHNICAL DATA SHEET

Synolac® 8038 S 75 (Formerly CHEMPOL® 809-2838)

PRODUCT APPLICATION DETAILS

Synolac® 8038 S 75 is a high solids chain-stopped TOFA short oil alkyd, with fast tack free times and good exterior durability and toughness, for use in agricultural and heavy-duty equipment c

SALES SPECIFICATIONS

	CHARACTERISTICS	METHODS
Solid content	75 %	-
Viscosity	Z2-Z4 Gardner Holdt	-
Color	12 Gardner	-
Acid value	8 mg KOH/g	-

OTHER CHARACTERISTICS¹

	CHARACTERISTICS	METHODS
Solvent	A100/n-Butanol	-
Density	8.8 lbs/gal	-
Hydroxyl content	2.6 %	-
Hydroxyl number	87	-

¹The data provided for these properties are typical values, intended only as guides, and should not be construed as sales specifications

MARKETS & APPLICATIONS

Coatings & Inks

- Industrial Coating
 - Ace
 - Automotive - OEM
 - Automotive - Refinish
 - General Industry

PERFORMANCE BENEFITS

- Fast Tack Free Time
- Good Exterior Durability
- Good Toughness
- Useful in Agricultural and Heavy-Duty Equipment Coatings
- Auto Refinish

SYNOLAC® 8038 S 75 (Formerly CHEMPOL® 809-2838)

PRODUCT SAFETY

Please refer to the corresponding Safety Data Sheet.

STORAGE AND HANDLING

Synolac® 8038 S 75 - Packaged products should be stored in a dry indoor location. The material should be stored in the original, unopened and undamaged container at storage temperatures not exceeding 85° F (30° C). Exposure to direct sunlight should be avoided. For assistance with the best practices for bulk shipment storage and handling contact Arkema.

Arkema Coating Resins
410 Gregson Dr.
Cary, NC 27511 – USA
T +1 919 469 6700

Headquarters: Arkema France
51, Esplanade du Général de Gaulle
92800 Puteaux – France
T +33 (0)1 49 00 80 80

Disclaimer - Please consult Arkema's disclaimer regarding the use of Arkema's products on <https://www.arkema.com/global/en/products/product-safety/disclaimer/> which is incorporated herein by reference and made a part hereof.
Arkema France, a French société anonyme registered at the Trade and Companies Register of Nanterre under the number 319 632 790

ARKEMA