

TECHNICAL DATA SHEET

TERRABLEND™ GL

Rheology modifier for glaze application

TYPICAL CHARACTERISTICS

Nature	Acrylic copolymer in aqueous dispersion
Appearance	Milky liquid
Solid Content (%)	30
pH	3
Brookfield viscosity (mPa.s)	2 to 25 mPas
Specific gravity	1.06

DESCRIPTION

Terrablend™ GL has been developed to stabilize oxides and pigments in glaze formulations.

RECOMMENDED ADDITION LEVEL

3 to 6% depending on pH

STANDARD PACKAGING

Other packaging may be available upon request

- 1000L IBC
- 220L Drum

HANDLING & STORAGE

The product can be irreversibly altered by frost. It should be protected from the effect of weathering and stored between 5 and 40°C. Once opened, packaging should be resealed immediately after use.

In these conditions, this product should be used within 6 months from delivery.

HEALTH AND ENVIRONMENTAL DATA

For safe handling please refer to the Safety Data Sheet. For more information about health and environmental data, please contact us.

MARKETS

Building & Construction

- Ceramics
- Tiles

KEY BENEFITS

- Functionality Rheology modifier
- Typical use Glazing

Headquarters: Arkema France
51, Esplanade du Général de Gaulle
92800 Puteaux – France
T +33 (0)1 49 00 80 80