

## TECHNICAL DATA SHEET

# TERRABLEND™ GS 17

Stabiliser and thickener for the glaze industry

### TYPICAL CHARACTERISTICS

Nature	<b>Acrylic copolymer in aqueous dispersion</b>
Appearance	<b>Low viscosity, white milky liquid</b>
Solid Content (%)	<b>30</b>
pH	<b>3</b>
Specific gravity	<b>1.06</b>

### DESCRIPTION

Terrablend™ GS 17 has been designed to stabilise oxides and pigments in glaze formulations.

### STANDARD PACKAGING

Other packaging may be available upon request

- 1000L IBC
- Bulk

### HANDLING & STORAGE

The product can be irreversibly altered by frost. It should be protected from the effect of weathering and stored between 5 and 40°C. Once opened, packaging should be resealed immediately after use. In these conditions, this product should be used within 6 months from delivery.

### HEALTH AND ENVIRONMENTAL DATA

For safe handling please refer to the Safety Data Sheet. For more information about health and environmental data, please contact us.

### MARKETS

#### Building & Construction

- Ceramics
  - Sanitary & Table Ware
  - Tiles

### KEY BENEFITS

- Functionality
  - Typical use
- Thickener  
Glazing

**Headquarters: Arkema France**  
51, Esplanade du Général de Gaulle  
92800 Puteaux – France  
T +33 (0)1 49 00 80 80

Disclaimer - Please consult Arkema's disclaimer regarding the use of Arkema's products on <https://www.arkema.com/global/en/products/product-safety/disclaimer/> which is incorporated herein by reference and made a part hereof.

Arkema France, a French société anonyme registered at the Trade and Companies Register of Nanterre under the number 319 632 790

[arkema.com](https://www.arkema.com)

**ARKEMA**